

The drawing shows a cross-section of a roof edge. On the left, a circular marker labeled "P1'" indicates the section line. The existing construction ("istniejąca konstrukcja") includes a concrete base, a green hatched insulation layer, a grey gravel drainage layer, and a red dashed line representing the EPDM membrane ("membrana EPDM"). A vertical dimension of 70-140 mm is shown for the insulation thickness at the edge.

On the right, the proposed construction ("projektowana poręcz Ø40") is detailed. It features a horizontal handrail with four circular cross-sections. Vertical dimensions from the top of the handrail down are: 80 mm, 92 mm, 40 mm, 89 mm, 700 mm, 240 mm, 240 mm, 240 mm, 400 mm, and 80 mm. Horizontal dimensions at the top are 330 mm, 250 mm, 80 mm, 40 mm, and 290 mm. Other vertical dimensions include 1110 mm, 898 mm, 1230 mm, 1390 mm, and 110 mm. A label "uchwyt punktowy do poręcz Ø40" points to the mounting bracket. At the bottom right, horizontal dimensions of 340 mm, 50 mm, and 80 mm are indicated. Section markers "2/2" are present at the top and bottom corners.

STROPODACH / TARAS
STAN PROJEKTOWANY

5cm	plytki betonowe 35x35x5 cm
4cm	żwir
	membrana EPDM
12cm	styrodur
	papa ze spadkiem
	warstwa spadkowa
	istniejąca konstrukcja

1. Wszystkie prace wykonać zgodnie ze sztuką budowlaną oraz obowiązującymi normami;
2. W razie wystąpienia problemów nie objętych opracowaniem, należy skontaktować się z projektantem;
3. Rzut należy rozpatrywać łącznie z przekrojem, szczegółem oraz opisem;
4. Przed przystąpieniem do robót budowlanych należy sprawdzić wymiary oraz ilości na miejscu budowy.

**BIURO PROJEKTOWE
ROSTEK PIOTR**

tel. 505 826 385
e-mail: piotrrostek@wp.pl

**MODERNIZACJA HOTELI "OLIMPIA"
W RYBNIKU - KAMIENIU
PRZY ULICY HOTELOWEJ 12**

RYBNIK - KAMIENÍ, ul. Hotelowa 12

inż. Piotr Rostek
upr. nr SLK/2442/PWOK/08

Kosch

MIASTO RYBNIK

ul. BOLESŁAWA CHROBREGO 2
44-200 RYBNIK

BUDOWLANA

PROJEKT TECHNICZNY

STAN PROJEKTOWANY
REMONT BALUSTRADY

mgr inż. Agnieszka Gajda

1:20

K-2