

The diagram is a detailed architectural cross-section of a building, showing the structural elements and construction details. The overall height of the building is 442 units. The roof is gabled, with a peak height of +4.40. The roof structure includes a ventilated space (przestrzeń wentylowana) and a gas pipe (gąsior z wentylacją blacha aluminiowa). The roof is covered with PIR insulation (gr. 5cm, pas szer. 40cm) and has a hidden gutter (rynna ukryta). The exterior walls are made of brick (cegła elewacyjna) with a metal roof edge (obróbka blacharska). The interior walls are also made of brick (cegła elewacyjna) and have a metal roof edge (obróbka blacharska). The floor is made of concrete slabs (płytki betonowe) with a 2% slope. The foundation is made of concrete (fundament pod ściankami działłowymi) and is located at a depth of -0.90. The ground level is at ± 0.00 = 75.32 m n.p.m. The diagram includes various dimensions and labels for different parts of the building, such as the roof, walls, floor, and foundation. Key dimensions include a total height of 442, a roof height of +4.40, a floor height of +3.04, and a foundation depth of -0.90. The diagram also shows the location of various structural elements, such as the roof, walls, floor, and foundation, and provides a detailed view of the construction details.

SZ.2	Warstwy ściany zewnętrznej CEGŁA ELEWACYJNA U=0,16W/m ² K (max. 0.20) ±16°C
60mm	plytki ceglane - klinkierowe
15cm	plyty polistyrenowe EPS 100 033 mocowanie mechaniczne i na zaprawie klejowej
24cm	blocczy silikatowe E24
	plytki gresowe na zapr. klej./ tynk cem. - wap.

D.2	Projektowane warstwy dachu (nad podcieniem)
0,7mm	blacha aluminiowa systemowa w kolorze antracyt na "rąbek stojący"
	warstwa rozdzielająca - mata podkładowa systemowa
2,5cm	deskowane
	krokwie
	przeźrzeń wentylowana strychu
16cm	płyta żelbetowa monolityczna
20cm	wełna skalna fasadowa montowana na klej i mechanicznie
1cm	tynk strukturalny metoda lekka mokra niepalny